

SAKO SPECIFICATION SAKO

SAKO 85 FINNLIGHT



SAKO 85 FINNLIGHT has a series of actions which are designated: Short actions Short (S) and Short Magnum (SM), Medium action (M) and Long action (L). All metal parts are made of stainless steel or are specially coated to ensure excellent wear and corrosion resistance in different weather conditions. Magazine bottom and trigger guard are made of hard anodized aluminium for reduced weight.

The ACTIONS continue to offer traditional SAKO features such as: action sizes matched to cartridges; mechanical ejection and integral tapered scope mount rail. Additionally there is a controlled feed on all models to ensure reliable cartridge feed to the chamber on all situations (Pat. pend.).

The MAGAZINE is detachable and it can also be loaded through the ejection port. Magazine release is prevented against accidental release (Pat.pend.).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged.

In two steps injection molded STOCK has softer grip areas in the pistol grip and fore-end sides and bottoms. Innovative recoil directing recoil pad.

SAKO 85 FINNLIGHT is available without open sights. Integral rails for the scope mounts are on the top of the receiver. The short, fluted, totally free-floating BARREL is cold hammer-forged of stainless steel.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length
S	22-250 Rem	14"	S 1030 mm (40 1/2")
	243 Win	10"	SM 1125 mm (44 5/16")
	260 Rem	8"	M 1085 mm (42 3/4")
	7mm-08 Rem	9.5"	L 1145 mm (45 1/16")
	308 Win	11"	
SM	270 Win Short Mag	10"	Barrel length
	300 Win Short Mag	11"	S 515 mm (20 1/4")
M	25-06 Rem	10"	M 570 mm (22 7/16")
	6.5x55 SE	8"	SM / L 620 mm (24 3/8")
	270 Win	10"	Weight
L	30-06 Sprg	11"	S 2.8 kg (6 3/16 lbs)
	7mm Rem Mag	9.5"	SM / M 2.9 kg (6 3/8 lbs)
	300 Win Mag	11"	L 3.1 kg (6 13/16 lbs)
			Length of pull
			S / SM / M / L 355 mm (14")
			Cartridge capacity
			S / M 6 rounds (1 in chamber, 5 in magazine)
			SM / L 5 rounds (1 in chamber, 4 in magazine)