



SPECIFICATION

TIKKA T3 SUPER VARMINT



ACTION

Based on a two locking lug T3 action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt and other steel parts are made of stainless steel.

MAGAZINE

The single-column detachable clip magazine holds 4-6 cartridges. Single-column 3-4-shot (depending on caliber) magazine is available as accessory.

TRIGGER

The single-stage trigger pull is adjustable from 2 to 4 lbs (1 to 2 kg). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

STOCK is made of glass-fiber reinforced copolymer polypropylene and has a buttplate system where the length of pull is adjustable by means of spacers. Height adjustable cheek piece and extra-wide forend carried out with add-ons. Straight stock features ambidextrous palm swell. Adjustable cheek piece can also be used by lefthanded shooter. Standard sling swivel studs under the fore-end and butt stock as standard. Extra sling swivel stud for bipod mounting included in the package. Military type sling swivel studs can be optionally attached in both sides of the butt stock and fore-end and under the butt stock and fore-end.

BARREL is heavy, totally free-floating and cold hammer-forged of stainless steel.

SIGHTS

TIKKA T3 SUPER VARMINT is available without open sights. Picatinny rail for the scope mounts on the top of the receiver is available option. Receiver drilled and tapped for Picatinny rail.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length
T3	204 Ruger	12"	T3 1110 mm (43 3/4")
	222 Rem	14"	Barrel length
	223 Rem	8"	T3 600 mm (23 3/4")
	223 Rem	12"	Weight
	22-250 Rem	14"	T3 3.7 kg (8 5/32 lbs)
	243 Win	10"	Cartridge capacity
	260 Rem	9"	T3 204 Ruger, 222 Rem, 223 Rem 7 rounds (1 in chamber, 6 in clip magazine)
	7mm-08 Rem	9,5"	T3 270 Win Short Mag, 300 Win Short Mag 4 rounds (1 in chamber, 3 in clip magazine)
	308 Win	11"	T3 other calibers 6 rounds (1 in chamber, 5 in clip magazine)
	270 WSM	10"	
	300 WSM	11"	
	25-06 Rem	10"	
	6.5 x 55 SE	8"	
	270 Win	10"	
	30-06 Sprg	11"	
	9.3x62	14"	
	7 mm Rem Mag	9.5"	
	300 Win Mag	11"	
	338 Win Mag	10"	